



Turbo-Centrifuge AZF-T40 Automatic discharge



Turbo-Separator

Suitable for separating particles from all sorts of industrial fluids.

» Technical information

AZF-T40	
Flowrate	1 to 200 LPM
Medium	Oil and Emulsion
PH	Standard Steel/Aluminium 6.5 to 9.5 Stainless Steel 4 to 14
Temperature	60° C / 90° C
Quality of cleanliness	Down to 1 µm possible
Material Housing	Steel / Stainless Steel
Material Rotor	Alu / Stainless Steel
Rotor capacity	40 dm ³
Sludge Volume	< 30 kg / hour
Type of cleaning	2 phase or 3 phase
Rotor Speed	2150 RPM to 2400 RPM
Separating Factor	950 to 1630 g (1 g = gravity acceleration)
Noise emission	< 70 dBA possible
Drive	Belt Drive (Frequency controlled)
Drive Power	7.5 kW
Solids discharge	Automatically
Liquid return	Under pressure
Controlpanel	Including
Inlet	Need a Feedpump
Dimension	> 800 x 1200 x 1300 mm
Weight	> 620 kg
Options	Inlet (dirty liquid) Tank Clean Liquid Tank Pumps Chiller / Heating System / Aircleaner Magnetic Prefilter

