



Usages:

The pumps are suitable to transfer liquids containing impurities measuring up to 2-3 mm. The hydraulic components, namely the brass impeller and the aluminium scroll and pump body allow the pumps to be used with water, emulsions and oily substances in general with a maximum viscosity of 3° Engler (° CST).

The temperature of the liquid must not exceed 90° C.

They are usually used on:

Machine tools

(milling machines – lathes - drills)

Glass processing machines

Filtration systems.

They should usually be installed on a tank, with a capacity in proportion to the flow rate, at about 4 – cm. from the bottom. It is important to check that the maximum level of the liquid in the tank always remains 3 – 4 cm. lower than the flange (see figure).

In cases where the liquid is particularly dirty, the user is recommended to construct the tank compartments to allow the dirt to deposit before it is stirred up by the pump.

For other usages you are advised to consult our technical office.






Table of dimensions and weights

TYPE	A mm	B mm	C mm	ØD mm	ØE mm	ØF mm	ØG mm	H mm	ØI mm	ØL mm	Kg.
MP 80C	517	230	287	1"	190	190	230	245	204	9 N. 5	16,50
	567	280									17,00
	642	355									17,50
	757	470									18,00
MP 90B	590	265	325	1"	190	190	230	255	204	9 N. 5	22,00
	640	315									22,50
	715	390									23,00
	830	505									23,50
MP 100B	625	265	360	1-1/4"	202	220	250	275	235	9 N. 5	32,00
	675	315									32,50
	725	365									33,00
	775	415									33,50
	955	595									35,50



Electrical features

TYPE	KW. Input	Hz. 50		Hz. 60			
		230/400	254-290/440-500	230/400	208-230/440-460	254-277/440-480	318-346/550-600
MP 80C	2,20	6,2/3,6	4,8/2,8	7,4/4,3	6,5/3,8	6,2/3,6	5,2/3,0
MP 90B	3,60	9,4/5,4	7,4/4,3	11,2/6,4	9,5/5,5	9,4/5,4	7,8/4,5
MP 100B	5,70	17,3/10	13,8/8,0	20,7/12	17,6/10,2	17,3/10	14,4/8,3



The data of this diagram are referred to a viscosity not higher than 5 CST 20° c.





Type MP 80 C

Type MP 90 B

Type MP 100 B

Components	Materials	Materials	Materials
1 Rod	Steel	Steel	Steel
2 Frame	Aluminium	Aluminium	Aluminium
3 V-ring Ø 20	NBR Ø 20	NBR Ø 25	NBR Ø 30
4 Rotor			
5 Stator			
8 Shaft	Steel C 40	Steel C 40	Steel C 40
9 Pump body	Aluminium	Aluminium	Aluminium
12 Impeller	Brass 58	Brass 58	Cast iron G20
14 Terminal box	Nylon	Nylon	Nylon
15 Terminal block	mm. 50x32 6P	mm. 50x32 6P	mm. 50x32 6P
16 Non-drive end shield	Aluminium	Aluminium	Aluminium
17 Fan	Nylon	Nylon	Nylon
18 Fan cover	Nylon***	Nylon***	Nylon***
19 Bearing	6305 ZZ	6305 ZZ	62207 2RS
21 Spring ring	Ø 47	Ø 52	Ø 62
22 Bearing	6204 ZZ	6205 ZZ	6206 ZZ
24 Drive end shield	Aluminium	Aluminium	Aluminium
25 Sealing ring	NBR 25x40x7	NBR 25x47x7	NBR 35x47x7
28 Bronze bearing	23x20x20	23x20x20	23x20x20
29 Sealing ring	NBR 20x32x5	NBR 20x32x5	NBR 20x32x5
31 House impeller	Aluminium	Aluminium	Aluminium
37 Diffuser	N. 1 Aluminium	N. 2 Aluminium	N. 2 Aluminium
41 OR ring	NBR 180X2	NBR 180X2	NBR 180X2
44 Spacer	Steel. 20X14X23,5	Steel 20X14X23	Steel 20X14X21
45 Spacer	No	Steel 20X14X22	Steel 20X14X21

