



Turbo-Coolant Cleaning Plant MZF-T10-3PH



Turbo-Separator

Suitable for separating particles and tramp oil from all sorts of industrial fluids in the tool and automotive industry.

» Technical information

MZF-T10-3PH	
Flowrate	1 to 10 LPM
Medium	Emulsion or spezial liquid
PH	Standard 6.5 to 9.5 Stainless Steel 4 to 14
Temperature	60° C
Quality of cleanliness	Down to 1 µm possible
Material Housing	Steel or Stainless Steel
Material Rotor	Aluminium or Stainless Steel
Rotor capacity	9 dm3
Sludge Volume	3 bis 5 kg
Type of cleaning	3 phase
Rotor Speed	50 Hz = 2850 RPM 60 Hz = 3400 RPM
Separating Factor	900 g to 1320 g (1 g = gravity acceleration)
Noise emission	< 72 dBa
Drive	Directdrive
Drive Power	2 kW
Solids discharge	Manual
Liquid return	Under pressure
Controlpanel	Including
Inlet	175 mm
Dimension	> 515 x 710 x 980 mm
Weight	> 270 kg
Options	Inlet Tank (dirty liquid) Clean Liquid Tank Pumps Chiller / Heating System / Aircleaner Magnetic Prefilter

