



Turbo-Centrifuge MZF-T14



Turbo-Separator

Suitable for separating particles and tramp oil from all sorts of industrial fluids.

» Technical information

MZF-T14	
Flowrate	1 to 150 LPM
Medium	Oil and Emulsion
PH	Standard 6.5 to 9.5 Stainless Steel 4 to 14
Temperature	60° C / 90° C
Quality of cleanliness	Down to 1 µm possible
Material Housing	Steel or Stainless Steel
Material Rotor	Aluminium or Stainless Steel
Rotor capacity	14 dm ³
Sludge Volume	6 bis 10 kg
Type of cleaning	2 gphase or 3 phase
Rotor Speed	2850 RPM to 3400 RPM
Separating Factor	1440 g to 2480 g (1 g = gravity acceleration)
Noise emission	< 75 dBa
Drive	Directdrive or frequency controlled
Drive Power	3.2 kW t 6 kW
Solids discharge	Manual
Liquid return	Under pressure
Controlpanel	Including
Inlet	85 mm (self priming)
Dimension	> 550 x 680 x 880 mm
Weight	> 200 kg
Options	Inlet Tank (dirty liquid) Clean Liquid Tank Pumps Chiller / Heating System / Aircleaner Magnetic Prefilter

